



JIANGSU RUNAU ELECTRONICS MANUFACTURING CO.,LTD

» 焊接二极管 | Welding Diode

特点:

- 超大电流能力
- 极低的通态电压
- 非常低的热电阻
- 高可靠性
- 适用于中频或高频

Features:

- High forward current capability
- Low forward voltage
- Minimum thermal resistance
- High operational reliability
- Suitable for intermediate or high frequency

应用领域:

- 逆变型电阻焊整流装置

Applications:

- Inverter resistance welding rectifying device



型号	I _{F(AV)}	T _C	V _{RRM}	I _{FSM} @T _{VJM} & 10ms	I ² t	V _{FM} @I _{FM} &T _J =25℃		T _{jm}	R _{jc}	F	m	外形
TYPE	A	℃	V	A	A ² s	V	A	℃	℃/W	KN	Kg	Outline
电压至 400V(Up to 400V)												
ZW7100--**	7100	85	200~400	55000	1.5 × 10 ⁷	1.05	5000	170	0.0100	24	0.140	W1
ZW10500--**	10500	85	200~400	70000	2.4 × 10 ⁷	1.01	5000	180	0.0050	32	0.460	W2
ZW12000--**	12000	85	200~400	85000	3.6 × 10 ⁷	0.99	5000	170	0.0060	35	0.205	W3
ZW13500--**	13500	85	200~400	85000	3.6 × 10 ⁷	0.97	5000	180	0.0039	35	0.140	W4
ZW16000--**	16000	85	200~400	120000	7.2 × 10 ⁷	0.92	5000	170	0.0040	37	0.570	W5
ZW18000--**	18000	85	200~400	135000	9.1 × 10 ⁷	0.90	5000	170	0.0040	40	0.580	W5

