



RUNAU

Jiangsu Runau Electronics Manufacturing Co.,Ltd

MDC600 MDA600 MDK600 MDX600

1200-2000V_{RRM}

GENERAL PURPOSE DIODE MODULE

Features:

- . Electrical insulation between chip and base plate, 2500V AC insulation
- . Compress structure
- . Excellent temperature characteristics and power cycling capability
- . Small size & light weight

Typical application:

- . AC / DC motor control
- . Various rectification power supplies
- . Frequency converter



ELECTRICAL CHARACTERISTICS AND RATINGS

Symbol	Parameter	Conditions	Tj(°C)	Data			Unit
				Min	Typ	Max	
I _{F(AV)}	Mean forward current	Sinewave 180°,50Hz Single side cooling, T _c =85°C	150			600	A
I _{F(RMS)}	RMS forward current		150			942	A
V _{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	V _{DRM} &V _{RRM} tp=10ms V _{DSM} &V _{RSM} =V _{DRM} &V _{RRM} +200V	25	800		1800	V
I _{RRM}	Repetitive peak off-state current	V _{DM} = V _{DRM}	150			30	mA
I _{RRM}	Repetitive peak reverse current	V _{RM} = V _{RRM}					
I _{FSM}	Surge forward current	10ms bottom width, half sine wave	150			19	KA
I ² t	I squared t	V _R =0.6V _{RRM}				1850	A ² s*10 ³
V _{FO}	Forward threshold voltage		150			0.75	V
r _F	Slope resistance					0.35	mΩ
V _{FM}	Peak forward voltage	I _{FM} =1800A	25			1.3	V
R _{th(j-c)}	Thermal impedance(junction to case)	180° sine wave, Single side heat dissipation				0.065	°C /W
R _{th(c-h)}	Thermal impedance(case to heatsink)	180° sine wave, Single side heat dissipation				0.024	°C /W
V _{iso}	Insulation voltage	50Hz,R.M.S,t=1min,I _{iso} :1mA(MAX)		2500			V
F _m	Electrode mounting torque (M6)				12		N·m
	Base plate mounting torque (M6)				6		N·m
T _{stg}	Storage temperature			-40		125	°C
W _t	Weight				1820		g




Fig.1 Forward Volt-ampere Characteristic Curve




Fig.2 Transient Thermal Impedance Curve




Fig.3 Max Power Dissipation Vs. Mean Forward Current




Fig.4 Max Case Temperature Vs. Mean Forward Current




Fig.5 Max Power Dissipation Vs. Mean Forward Current




Fig.6 Max Case Temperature Vs. Mean Forward Current




Fig.7 Surge Current Vs.Cycles





Fig.8 I^2t Vs.Time

OUTLINE



M466F

