



R U N A U

Jiangsu Runau Electronics Manufacturing Co.,Ltd

ZP2400-Rectifier Diode


5400~6500 V_{RRM}

GENERAL PURPOSE HIGH POWER STANDARD RECTIFIER

Features:

- . All Diffused Structure
- . High Surge rating
- . Blocking capability up to 6500 volts
- . Ceramic Housing Hermetic Package
- . Pressure Assembled Device

ZT95cT



ELECTRICAL CHARACTERISTICS AND RATINGS

Reverse Blocking

Device Type	V _{RRM} (1)	V _{RSM} (1)
ZP2400-54	5400	5600
ZP2400-56	5600	5800
ZP2400-58	5800	6000
ZP2400-60	6000	6200
ZP2400-65	6500	6700

V_{RRM} = Repetitive peak reverse voltage

V_{RSM} = Non repetitive peak reverse voltage (2)

Repetitive peak reverse leakage	I _{RRM}	5 mA 200 mA (3)
---------------------------------	------------------	--------------------

Notes:


All ratings are specified for T_j=25 °C unless otherwise stated.

(1) All voltage ratings are specified for an applied 50Hz/60Hz sinusoidal waveform over the temperature range 0 to +150°C.

(2) 10 msec. max. pulse width

(3) Maximum value for T_j = 150°C.

(4) See parameter definition below:



REVERSE RECOVERY CHARACTERIST

Conducting - on state

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Average value of on-state current	I _{F(AV)}		2400		A	Sinewave, 180°, T _c =100°C
RMS value of on-state current	I _{FRMS}		3768		A	Nominal value
Peak one cycle surge (non repetitive) current	I _{FSM}		36000		A	10 msec (50Hz), sinusoidal wave-shape, 180° conduction, T _j = 150 °C
I square t	I ² t		6.5 × 10 ⁶		A ² s	10 msec
Peak on-state voltage	V _{FM}		1.50		V	I _{FM} = 5000A; T _j =25°C
Threshold voltage	V _{FO}		0.95		V	T _j =150°C, I=0.5π I _{F(AV)} to 1.5π I _{F(AV)}
Slope resistance	r _F		0.11		mΩ	T _j =150°C, I=0.5π I _{F(AV)} to 1.5π I _{F(AV)}
Reverse Recovery Current (4)	I _{RM(REC)}				A	I _{FM} = 500 A; di/dt = -10 A/s; T _j max
Reverse Recovery Charge (4)	Q _{rr}			7000	μC	I _{FM} = 500 A; di/dt = -10 A/s; T _j max
Reverse Recovery Time (4)	t _{rr}				μs	I _{FM} = 500 A; di/dt = -10 A/s; T _j max

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Operating temperature	T_j	-40	+150		$^{\circ}\text{C}$	
Storage temperature	T_{stg}	-40	+150		$^{\circ}\text{C}$	
Thermal resistance - junction to case	$R_{\Theta(j-c)}$		0.008		$^{\circ}\text{C/W}$	Double sided cooled
Thermal resistance - case to heatsink	$R_{\Theta(c-s)}$		0.002		$^{\circ}\text{C/W}$	Double sided cooled
Mounting force	P	55	65	60	kN	
Weight	W			1.40	kg.	

* Mounting surfaces smooth, flat and greaseless

CASE OUTLINE AND DIMENSIONS

